

## CSP-P Seismic Energy Source



The **CSP-P** is a small, light 350 Joule power source intended primarily as a boomer power supply but it can be used with small sparkers.

Recently upgraded, the CSP-P now incorporates dual-voltage technology that allows the operator to tune the sound source to a particular application for improved data quality.

### Key Features

- Incorporates dual-voltage technology for exceptional versatility
- Variable Input Power Circuitry for 'soft start'
- Proprietary pulse shaping circuitry for high resolution data
- Additional safety/protection features
- All settings externally selectable
- LED fault indicators
- High current and voltage solid state (semi-conductor) discharge method
- Meets EC emissions regulations enabling interference-free field use
- Supplied in robust transit case, with HV junction box (HVJ2000), mains lead and HV connector plug

## Technical Specification

### PHYSICAL

Size	Transit Case (4U) with cover in place and handles flat: 29cm(H) x 56cm(W) x 56cm(D)
Weight	CSP-P, case and cover: 35kg

### ELECTRICAL SPECIFICATION

Mains Input	110 or 240Vac (fixed) 45-65Hz@2.0kVA single phase. 3 pin connector Variable Input Power Circuitry (AVIP) 'soft start' circuitry
Voltage Output	2500 to 3950 Vdc, 4 pin interlocked connector Solid state semi-conductor discharge method
Output Energy	Easy switch selectable in increments 50,100,150,200,300 and 350 Joules
Charging Rate	1500J/second for continuous operation at 0-45°C ambient

## CSP-P Technical Specification continued...

Capacitance	48 $\mu$ F at 10 <sup>8</sup> shot life
Trigger	+ve key opto isolated or isolated closure set by front panel switch BNC connector on front panel and remote box (optional)
Repetition rate	6pps max Limited by charge rate, energy level and sound source rating
Earth	M8 stainless steel stud on front panel

### SAFETY FEATURES

- Main electronic control circuits and secondary layer of safety circuitry
- Specially designed HV connector with interlock
- High speed dump resistors for high voltage components
- Capacitor bleed resistors
- Open circuit shutdown
- Timer shutdown
- Output current monitor and shutdown
- Over temperature shut-down
- Cover and connector interlocks
- HV fault indicator for internal temperature, low input voltage or capacitor fault
- Remote control available for triggering and operation

*The unit's internal design has a modular construction for ease of servicing and capacitor replacement. However, for safety reasons, only Applied Acoustics trained engineers should attempt a repair.*

### COMPATIBLE SOUND SOURCES

AA201, AA251 and AA301 Boomer plates  
Squid 501 Sparker



Due to continual product improvement, specification information may be subject to change without notice.  
CSP-P Seismic Energy Source/June 2015  
©Applied Acoustic Engineering Ltd.



#### Applied Acoustic Engineering Ltd

T +44(0)1493 440355  
F +44(0)1493 440720  
E [general@appliedacoustics.com](mailto:general@appliedacoustics.com)  
W [www.appliedacoustics.com](http://www.appliedacoustics.com)